

POLYON[®] SYNTHETIC MOTOR OIL CJ-4 / SN

XL-0831 POLYON[®] Synthetic Motor Oil is a “state of the art” fully synthetic motor oil that has been formulated with P.T.F.E. resin (Teflon[®]) to meet the demands for superior lubrication in today's engines.

XL-0831 POLYON[®] Synthetic Motor Oil, with its inherent high VI characteristics, will facilitate low-temperature engine starting.

Environmental concerns regarding emissions and their control require that engines run hotter and faster. These demands produce a situation that requires engine oils to have higher cooling and lubricating qualities. Extended valve-train warranties, turbo and injection systems also require superior engine oils that will not break down under severe operating conditions.

XL-0831 easily meets the challenge.

XL-0831 POLYON[®] Synthetic Motor Oil is available in all standard SAE grades.

XL-0831 POLYON[®] Synthetic Motor Oil is fortified with a proven detergent package CJ-4 / SN will outperform SL / CI-4, CI-4PLUS oils.

TYPICAL SPECIFICATIONS

Product Code: XL-0830	/053	/054	/103	/104	/154	/205	/030	/040	/050
SAE Grade	5W30	5W40	10W30	10W40	15W40	20W50	30	40	50
Viscosity (cst @ 40°C) (ASTM D-445)	60.3	84.0	62.3	92.3	97.2	145	62.5	90.3	152
(cst @ 100°C) (ASTM D-445)	10.5	13.0	11.5	13.7	14.3	18.9	11.8	13.3	17.2
Viscosity (cP @ -25°C) (ASTM D-2983)	2700	3300	-	-	-	-	-	-	-
(cP @ -20°C) (ASTM D-2983)	-	-	3050	3200	-	-	-	-	-
(cP @ -15°C) (ASTM D-2983)	-	-	-	1680	3000	4800	-	-	-
Viscosity Index	165	155	182	151	151	148	188	148	124
Flash Point (°C)	200	203	203	204	208	235	220	235	240
Pour Point (°C)	-53	-50	-43	-40	-39	-35	-35	-30	-18
Pumpability (°C)	-39	-50	-36	-34	-29	-20	-	-	-
Maximum Temperature (°C)									
Specific Gravity (g/ml)	0.86	0.86	0.86	0.87	0.88	0.88	0.87	0.87	0.88
Total Base Number (TBN)	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5
Colour									

Teflon[®] is a Registered Trademark of DuPont.
POLYON[®] is a Registered Trademark of Thermal-Lube Inc.



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge, accurate. It is intended to be helpful, and is not to be considered a guarantee.



XL-0831 meets all of the following OEM specifications:

API (American Petroleum Institute)	CJ-4, CI-4, CI-4 PLUS, CH-4, CF-4, SN, SM, SL, SJ, SH, SG, SF, "Energy Conserving" (EC-II) "Fuel saving"
Daimler Chrysler	228.1 Blanket, 229.1 Blanket
Ford	ESE-M2C153 E
General Motors	6085 M
JASO (JAPAN).....	M328-83, M331-84, M333-86
U.S. Army	MIL-L-46152 D, MIL-L-21260, MIL-L-2104E
Volkswagen.....	500.00, 501.01, 505.00
MACK.....	EO-N Premium Plus 03
Cummins	CES 20078, CES 20076, CES 20072
ACEA.....	E2/E5/E7
MAN	271
Volvo	VDS-2
MTU	Type 2
DDC	Series 2000/4000 Category 1; Power Guard
ILSAC.....	GF-Compliant
Caterpillar	ECF-1&2
MB.....	228.3



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

