

HYBRID SYNTHETIC GREASE DGG

XL-0925 is a unique 100% hybrid synthetic oil-based, hydrophobic bearing grease formulated to withstand extremely high static pressures at very low and intermittent RPM.

The blend of synthetic base oils and performance enhancing additives selected to formulate **XL-0925** were chosen for their individual inherent chemical and physical characteristics. Priority attributes were assigned to **endurance, non-toxicity, and biodegradability** in aqueous environments.

The exceptionally high base-oil viscosity index (VI) and low temperature fluidity enables **XL-0925** to provide efficient lubrication over a wide range of temperature, from -50°C to 200°C.

Low and intermittent bearing RPM inhibits the ability of most conventional lubricants (greases) to form a stable lubricating elasto-hydrodynamic (EHD) film. Under heavy loads, rollers will come in contact with the bearing race rings, and scoring will occur upon initial rotation, unless an appropriate boundary lubricant protects contacting metallic surfaces.

Unlike conventional lubricants, **XL-0925** has been designed to perform like a "lubricant sponge" releasing a **non-toxic** and **chemically inert** graphite film to be deposited on the contact areas of friction, providing the necessary lubrication to the rollers. Excess graphite will be re-absorbed into the "lubricant sponge" once the roller has passed over the surface.

XL-0925 is formulated for use in sluice gates, intake gates, and any other application requiring a non-toxic, partially biodegradable, hydrophobic EP grease in high loaded bearings.



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com



TYPICAL SPECIFICATIONS

Product Code: XL-0925	/102	/202
N.L.G.I. Grade:	2	2
Penetration @ 25°C (ASTM D-217)		
After 60 strokes	268	265
After 10,000 strokes	290	305
Dropping Point (°C) (ASTM D-2265)	None	None
Melting Point (°C)	None	None
Copper Strip Test (163°C for 3 hours)	Negative	Negative
Texture	Smooth/tacky	
Colour	Dark gray	
Type of thickener	Silica	
Oil Separation (24hrs @ 25°C) (ASTM D-1742)	< 1%	< 1%
Additives	Carbon/Graphite	
Temperature Range (°C)	-50 to 200	
Minimum Dispensing Temperature (°C)	-66	-62
Maximum Intermittent Temperature (°C)	250	250
Base Oil Viscosity (cSt @ -30°C) (ASTM D-445)	39,700	20,300
(cSt @ 0°C) (ASTM D-445)	7,450	3,000
(cSt @ 30°C) (ASTM D-445)	3,000	800
(cSt @ 40°C) (ASTM D-445)	2,100	600
(cSt @ 100°C) (ASTM D-445)	440	105
Base Oil Viscosity Index	378	273



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
 Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

