

## GENERAL PURPOSE SYNTHESIZED GREASE

**XL-0GP2** is a general purpose grease formulated specifically to meet the requirements for extremely heavy loads. The Extreme Pressure, Anti-Wear, and Rust & Oxidation additives in this grease ensure that this versatile grease can be used in a variety of applications, such as bearings, pins, bushings, slide ways, as well gears and couplings requiring grease.

**XL-0GP2** can be used in applications in extreme environments with temperatures between -30°C and 250°C. Its inherent mechanical stability over this temperature range guarantees the lubrication of parts where conventional liquid and semi-liquid lubricants would fail.

**XL-0GP2** is formulated using severely hydrotreated High VI base stocks which enhances the overall quality of the grease and reduces the need for re-lubrication. This translates into less maintenance and increased productivity.

### FEATURES:

- Practically waterproof
- Non melting
- Extremely resistant to heavy loads
- Reduces friction
- Energy efficient
- Rust and oxidation resistant
- Reduces wear
- Wide temperature range

TYPICAL SPECIFICATIONS	
<b>Product Code: XL-0GP2</b>	<b>/002</b>
N.L.G.I. Grade:	2
Penetration @ 25°C (ASTM D-217)	
After 60 strokes	260
After 10,000 strokes	265
After 60,000 strokes	275
Dropping Point (°C) (ASTM D-2265)	None
Melting Point (°C)	None
Copper Strip Test (163°C for 3 hours)	1A
Texture	Tacky
Colour	Red
Timken OK Load (lbs) (ASTM D-2509)	80 <sup>+</sup>
Type of thickener	Inorganic
Oil Separation (24hrs @ 25°C) (ASTM D-1742)	< 2%
Additives	EP, AW, R&O
Temperature Range (°C)	-30 to 250
Maximum intermittent Temperature (°C)	260
Minimum Dispensing Temperature (°C)	-20
Base Oil Viscosity (cSt @ 40°C) (ASTM D-445)	140



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

