

SEMI-SYNTHETIC LITHIUM COMPLEX GREASE

XL-0LC1 is designed to respond to the demands of extremely heavy loads. The EP, anti-wear, and Rust & Oxidation additives in this grease guarantee that parts will remain adequately lubricated where liquid or semi-liquid lubricants would fail.

ADVANTAGES:

- Practically waterproof
- Non-melting
- Resistant to heavy loads
- Prevents rust and corrosion
- Reduces wear

TYPICAL SPECIFICATIONS	
Product Code: XL-0LC1	/015
N.L.G.I. Grade:	1.5
Penetration @ 25°C (ASTM D-217)	
After 60 strokes	290
After 10,000 strokes	300
After 60,000 strokes	315
Melting point (°C)	> 260
Texture	Tacky
Timken OK load (kg) (ASTM D-2509)	30
Thickener	Lithium complex (modified)
Oil Separation (24hrs @ 25°C) (ASTM D-1742)	< 1%
Additives	EP, AU
Temperature Range (°C)	-45 to 150
Minimum temperature (pumpability) (°C)	-50



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

