

LITHIUM COMPLEX GREASE WITH GRAPHITE FOR HIGH TEMPERATURES

XL-0LC2/400 Series grease responds specifically to meet the requirements for heavy loads at moderately high temperature applications.

The EP, AW, R&O, and graphite additives in this grease guarantee the lubrication of parts where liquid and semi-liquid lubricants fail.

CHARACTERISTICS:

- Resistant to heavy loads
- Water resistant
- Rust resistant
- Reduces wear

TYPICAL SPECIFICATIONS	
Product Code: XL-0LC2	/402
N.L.G.I. Grade:	2
Penetration @ 25°C (ASTM D-217)	
After 60 strokes	265
After 10,000 strokes	270
After 60,000 strokes	280
Melting Point (°C)	> 260
Texture	Tacky
Timken OK Load (kg) (ASTM D-2509)	30
Type of thickener	Lithium complex
Oil Separation (24hrs @ 25°C) (ASTM D-1742)	< 2%
Additives	EP, AW, R&O, Graphite
Temperature Range (°C)	15 to 300
Minimum Temperature (°C)	10



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

