

## SYNTHETIC MOLYGRAPH® NON MELTING GREASE FOR PINS AND BUSHINGS

**XL-0EP2** is a special synthetic non-melting heavy duty grease containing the added protection on Molybdenum and Graphite for further reduction of friction and wear.

**XL-0EP2** is excellent for use on chassis, universal joints, bearings, ball joints and fifth wheel applications.

**XL-0EP2** is a general-purpose grease that is ideally suited for automotive, industrial, construction and farming purposes.

TYPICAL SPECIFICATIONS		
Product Code: XL-0EP2	/001	/002
N.L.G.I. Grade:	1	2
Penetration @ 25°C (ASTM D-217)	315	265
After 60 strokes	325	265
After 10,000 strokes	335	270
After 60,000 strokes	335	275
Dropping Point (°C) (ASTM D-2265)	None	
Melting Point (°C)	None	
Copper Strip Test (163°C for 3 hours) (ASTM D-4048)	Negative	
Texture	Buttery	
Colour	Black	
Timken OK Load (kg (lbs)) (ASTM D-2509)	34 (75) Typical	
Type of thickener	Inorganic	
Oil Separation (24hrs @ 25°C) (ASTM D-1742)	1% maximum	
Additives	MoS <sub>2</sub> , Graphite	
Temperature Range (°C)	-40 to 204	
Minimum Dispensing Temperature (°C)	-40	-50
Toxicity	Slight oral, minimal	



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

