

SYNTHETIC GEAR OIL FOR HEAVY DUTY POWER TRAINS

The **XL-2838** series of Synthetic Lubricants is formulated for manual gearboxes, jet pumps, and chain drives. They are blended to meet SAE and AGMA specifications.

The **XL-2838** series offer:

- All climate, year-round performance
- Improved component protection
- Easier cold weather shifting
- Less oil changes

TYPICAL SPECIFICATIONS				
Product Code: XL-2838	/050	/801	/759	/150
SAE Grade	50	80W140	75W90	-
ISO Grade	-	5-6 EP	4 EP	4 EP
Viscosity (cst @ 100°C) (ASTM D-445)	18.0	31.3	17.5	18.0
(cst @ 40°C) (ASTM D-445)	138.2	254.1	136.5	150.0
Viscosity (cP @ 0°C) (ASTM D-2983)	1,250	-	-	-
(cP @ -18°C) (ASTM D-2983)	-	20,500	7,125	-
(cP @ -26°C) (ASTM D-2983)	11,250	90,000	-	-
(cP @ -40°C) (ASTM D-2983)	270,000	-	150,000	-
Viscosity Index	154	165	141	124
Flash Point (°C) (ASTM D-92)	235	207	207	238
Pour Point (°C) (ASTM D-97)	< -40	< -32	< -45	< -40
API Gravity @ 15°C (ASTM D-287)	24.4	22.3	24.3	31.6
FZG Gear Test:	12+	11	11	12+
Foam Test (ASTM D-892) Sequence 1:	Pass	Pass	Pass	Pass
Sequence 2:	Pass	Pass	Pass	Pass
Sequence 3:	Pass	Pass	Pass	Pass
Copper Strip Test (3 hours @ 100°C)	Pass	Pass	Pass	Pass
(3 hours @ 121°C)	Pass	Pass	Pass	Pass



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge, accurate. It is intended to be helpful, and is not to be considered a guarantee.

