

FUEL TREATMENT FOR GASOLINE OR DIESEL ENGINES

XL-3000 is a special multifunctional formulation to provide superior performance with tangible economic benefits to owners and operators of today's diesel-powered vehicles - ranging from light- through heavy-duty service. **XL-3000** is designed for application treatment directly to bulk storage reservoirs, terminals, user holding tanks, or applied to the vehicles themselves.

XL-3000 provides the following benefits:

- Greater fuel efficiency
- Maximum power
- Minimum emissions
- Maximum operational dependability
- Extended service life
- Minimum maintenance by providing cleanliness to the overall fuel system
- Cleans injectors and lubricates pump
- Lubricates injectors and power zone region
- Supplements dispersancy of engine oil
- Dispersancy of insoluble gum which can occur during fuel storage
- Protects against corrosion of complete fuel system
- Low temperature flow improvement through wax crystal modification
- Rapid water separation

Used as recommended, **XL-3000** will not only keep engines and fuel systems clean, but will also help clean up pre-formed deposits that may interfere with injector atomization.

APPLICATION:

Recommended for use at:

One part **XL-3000** to 3000 parts fuel (1:3000)

0.03% by volume

250 ml / 750 liters fuel

TYPICAL CHARACTERISTICS	
Product Code: XL-3000	
Specific Gravity (g/ml @ 15.6°C)	0.909
Specific Gravity (lb/USG @ 60°F)	7.6
Viscosity (cSt @ 40°C) (ASTM D-445)	34.0
Nitrogen (% weight)	1.09 - 1.33



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

