

CETANE TREATMENT FOR DIESEL FUEL

XL-3001 is a special multifunctional formulation to provide superior performance with tangible economic benefits to owners and operators of today's diesel-powered vehicles - ranging from light through heavy-duty service. **XL-3001** is designed for application treatment directly to bulk storage reservoirs, terminals, user holding tanks, or applied to the vehicles themselves.

XL-3001 provides the following benefits:

- Increases the cetane level in diesel fuels
- Greater fuel efficiency
- Maximum power
- Minimum emissions
- Maximum operational dependability
- Extended service life
- Minimum maintenance by providing cleanliness to the overall fuel system
- Cleans injectors and lubricates pump
- Lubricates injectors and power zone region
- Supplements dispersancy of engine oil
- Dispersancy of insoluble gum which can occur during fuel storage
- Protects against corrosion of complete fuel system
- Low temperature flow improvement through wax crystal modification
- Rapid water separation

APPLICATION:

Recommended for use at a dilution of 1:1200 (one part **XL-3001** to 1200 parts fuel)

TYPICAL SPECIFICATIONS	
Product Code: XL-3001	/000
Viscosity (cSt @ 40°C) (ASTM D-445)	8.3
Flash Point (°C)	143
Copper Strip Test (163°C for 3 hours)	Pass
Vapour Pressure (mmHg @ 20°C)	0.2
Boiling Range (°C) (ASTM D-86)	182 to 367
Specific Gravity (g/ml)	0.84
Colour	Gold



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

