

## WATER-DISPLACING PENETRATING OIL

**XL-6330** is a uniquely formulated penetrating oil designed to displace water, remove rust and lubricate metal surfaces. Once applied, **XL-6330/005** will leave a fine long-chain polymer film that will protect metal surfaces from rust, and prevent new rust from forming.

**XL-6330/005** Can be applied by spray, brush or dip methods.

### TYPICAL CHARACTERISTICS:

- Contains no solids
- Excellent cleaning properties
- Will soften residual lubricant deposits
- An efficient EP lubricant
- Reduces energy consumption by reducing friction on moving parts
- Water displacing formulation
- Excellent salt water resistance
- Compatible with mineral oils and most synthetic base stocks
- High chemical stability
- Excellent low temperature properties
- High dielectric strength

TYPICAL SPECIFICATIONS	
<b>Product Code: XL-6330</b>	<b>/005</b>
Flash Point with solvent (°C)	61
without solvent (°C)	200
Specific Gravity (g/ml)	0.89
Pour Point (°C)	-60
Volatility (%)	> 45
Boiling Point (°C)	180
pH	6-7
Dielectric force (kV) (ASTM D-877)	> 25



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | [www.thermal-lube.com](http://www.thermal-lube.com)

