

## PENETRATING OIL

**XL-6331** is a uniquely formulated penetrating oil designed to displace water, remove rust and lubricate metal surfaces.

**XL-6331**, once applied, will leave a fine long chain polymer film to protect metal surfaces from rust.

### TYPICAL CHARACTERISTICS:

- Contains no solids.
- Will soften residual lubricant deposits.
- An efficient EP lubricant.
- Reduces energy consumption by reducing friction on moving parts.
- Water displacing formulation.
- Excellent salt water resistance.
- Compatible with mineral oils and most synthetic base stocks.
- High chemical stability.
- Excellent low temperature properties.
- High dielectric strength.

### Application:

**XL-6331** can be applied by spray, brush or dip method.

TYPICAL SPECIFICATIONS		
Product Code: XL-6331	/200	/201
Flash Point with solvent (°C)	61	61
without solvent (°C)	200	200
Specific Gravity (g/ml)	0.89	0.89
Pour Point (°C)	-60	-60
Volatility (%)	>45	>45
Boiling Point (°C)	180	180
pH	6-7	6-7
Dielectric force (ASTM D-877)	>25kV	>25kV



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

