

WATER SYSTEM TREATMENT

XL-6385 functions as a protective corrosion inhibitor and scale suppressant. It helps to keep water systems free from corrosive attack and harmful insulating deposits that may occur within non-treated systems.

XL-6385:

- Is compatible with ethylene-glycol-based anti-freezes.
- Will not affect non-metallic materials in engine cooling systems.
- Protects all ferrous and non-ferrous metals in water systems from corrosive attack.
- Provides cavitation-erosion protection.
- Extends equipment life and reduces maintenance time and costs.
- In **liquid form** for simple addition **directly** to the water system.
- Treated water does not cause dermatitis or other skin conditions diluted.

TYPICAL SPECIFICATIONS:

Appearance	Liquid
Colour	Clear, Red
Odour	None
Freeze-thaw recovery	Complete
Solubility	Completely Soluble in water
pH (100% concentration)	12
pH (1% concentration)	10.5

DOSAGE:

To assure a clean system, free from corrosion and scale deposits, add one litre of **XL-6385** to 72 litres of water as an initial treatment. A makeup dosage of 1% by volume of system capacity should be added every 500 to 1000 operating hours for open-bath type systems.

HANDLING (Concentrate):

- Handle like any alkali. **Avoid contact with skin. Do not take internally.**
- Product may be stored up to one year.



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

