

WIRE ROPE AND CHAIN LUBRICANT FIELD DRESSING & RUST PREVENTATIVE

XL-6501 is a solvent cut Wire Rope Field Dressing that should be applied immediately after a rope has been installed, to protect against the potential onset of corrosion within the core.

The solvent-cut **XL-6501** offers the following advantages:

- Softens old dressing materials to make the rope more receptive to new dressing.
- Penetrates all the way to the rope core
- Evaporates quickly, allowing the rope to be used shortly after dressing
- Provides Extreme Pressure lubrication
- Protects against the corrosive effects of water and brine
- Water emulsifying (slight)
- Excellent low temperature flexibility
- Resists excessive dirt pick-up

APPLICATION:

XL-6501 is effectively applied when the rope is in motion, and preferably while it is being bent over a sheave or pulley. Bending opens the spaces between the strands so that the dressing can penetrate to the interior and ultimately the rope core.

When using **XL-6501** to lubricate chains, be sure to apply the product directly into the link pins, and in thin layers.

XL-6501 may be further diluted with compatible solvents to the consistency desired for application by spray, brush, or dip coating.

REMOVAL: **XL-6501** may be removed with petroleum solvents.

TYPICAL PROPERTIES:

Density	0.865 g/ml
Flash Point (minimum, dry)	232 °C
5% Salt Spray	60+ days
Humidity Cabinet	60+ days
Colour	Clear / Yellow



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

