

SEMI-SYNTHETIC HYDRAULIC OIL

XL-7305 is formulated to meet the specific needs of industry and automobiles. In fact, **XL-7305** has proven its stability from one temperature extreme to the other, as well as preventing leaks. Added to this, **XL-7305** possesses a high viscosity index, a low pour point and a very low coefficient of friction.

XL-7305 is a superior oil ideally suited for wide temperature ranges. **XL-7305** is extremely resistant to chemical degradation, oxidation, wear and foam.

XL-7305 is available in all ISO standard grades as well as multi-grades for year-round applications.

TYPICAL SPECIFICATIONS						
Product Code: XL-7305	/022	/032	/046	/068	/100	/220
SAE Grade	-	5W	10W	20W20	20W40	220
ISO Grade	22	32	46	68	100	220
Viscosity (cSt @ 40°C) (ASTM D-445)	23.7	31.8	44.2	63.2	95.4	221
Viscosity (cSt @ 100°C) (ASTM D-445)	4.8	5.8	7.3	9.9	13.5	22.0
Viscosity Index	126	126	128	141	142	121
Flash Point (°C)	182	185	188	200	208	241
Pour Point (°C) (ASTM D-97)	-53	-52	-46	-38	-38	-35
Carbon Residue (ASTM D-189)	0.05	0.06	0.07	0.07	0.07	0.08
Minimum Operating Temperature (°C)	-48	-47	-41	-33	-33	-30
Maximum Operating Temperature (°C)	180	190	200	200	200	200



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge, accurate. It is intended to be helpful, and is not to be considered a guarantee.

