

## SYNTHETIC PAO INDUSTRIAL GEAR OIL WITH MOLYBDENUM

**XL-7310** series are fully formulated 100% synthetic based gear lubes that offer optimum performance in the broadest range of ambient temperatures and environmental conditions, with the added protection of Molybdenum.

**XL-7310** series provides:

- Energy conservation due to reduced friction.
- Solid film boundary lubrication for extreme pressure
- Component wear reduction.
- Reduced oil consumption.
- Compatibility with mineral oils.
- Increased maintenance intervals.
- High and low temperature viscosity stability.

TYPICAL SPECIFICATIONS											
Product Code: XL-7310	/759	/801	/809	/090	/140	/150	/220	/320	/460	/680	/999
SAE Grade	75w90	80w140	80w90	90	140	-	-	-	-	-	-
ISO Grade	-	-	-	-	-	150	220	320	460	680	1000
AGMA Grade	4 EP	5-6 EP	4 EP	5 EP	6 EP	4 EP	5 EP	6 EP	7 EP	8 EP	-
Viscosity (cSt @ 40°C) (ASTM D-445)	130	240	135	107	263	148	225	310	475	664	1100
Viscosity (cSt @ 100°C) (ASTM D-445)	17.5	31.0	18.0	14.2	26.4	18.7	25.9	32.4	42.0	54.0	75
Viscosity Index	148	171	149	135	132	142	147	145	138	141	139
Flash Point (°C)	207	220	208	210	235	235	235	238	238	238	255
Pour Point (°C) (ASTM D-97)	-50	-40	-47	-36	-30	-30	-32	-28	-22	-19	-12
Colour	Black / opaque										



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | [www.thermal-lube.com](http://www.thermal-lube.com)

The information presented in this bulletin is, to the best of our knowledge, accurate. It is intended to be helpful, and is not to be considered a guarantee.

