

## SYNTHETIC AUTOMOTIVE GEAR OIL GL-5

**XL-7315** series are 100% synthetic, fully formulated automotive (GL-5) gear lubes that offer optimum performance in the broadest range of ambient temperatures and environmental conditions.

**XL-7315** series provides:

- Energy conservation due to reduced friction
- Component wear reduction
- Reduced oil consumption
- Compatibility with mineral oils
- Increased maintenance intervals
- High and low temperature viscosity stability

| TYPICAL SPECIFICATIONS               |       |        |       |       |       |       |
|--------------------------------------|-------|--------|-------|-------|-------|-------|
| Product Code: XL-7315                | /759  | /801   | /890  | /090  | /140  | /220  |
| SAE Grade                            | 75W90 | 80W140 | 80W90 | 90    | 140   | --    |
| ISO Grade                            | --    | --     | --    | --    | --    | 220   |
| AGMA Grade                           | 4 EP  | 5-6 EP | 4 EP  | 5 EP  | 6 EP  | 5 EP  |
| Viscosity (cSt @ 40°C) (ASTM D-445)  | 115   | 240    | 135   | 107   | 263   | 225   |
| Viscosity (cSt @ 100°C) (ASTM D-445) | 18.5  | 31.0   | 18.0  | 14.2  | 26.4  | 25.9  |
| Viscosity Index                      | 180   | 171    | 149   | 135   | 132   | 147   |
| Flash Point (°C)                     | 207   | 220    | 208   | 210   | 235   | 235   |
| Pour Point (°C) (ASTM D-97)          | -50   | -40    | -47   | -36   | -30   | -32   |
| Colour                               | Green | Green  | Green | Green | Green | Green |



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | [www.thermal-lube.com](http://www.thermal-lube.com)

