

SYNTHETIC HYDRAULIC TACKY OIL

The **XL-7326** series of products is formulated to meet specifications for both industrial and automotive applications where the need for high quality synthetic hydraulic oil exists.

XL-7326 is made from a careful blend of high VI (viscosity index) synthetic base-stocks and polymer tackifiers, and will remain stable over a wide temperature range.

XL-7326 is formulated with all the necessary additives required to meet the specifications as an anti-wear, anti-rust, anti-oxidation, high quality oil and is recommended for use in circulating hydraulic systems *including* Paper Machine Oils.

XL-7326 is available in most standard ISO viscosity grades and in a four-season multi-grade as well. Because of the high quality of the product, we recommend up to 8,000 hours of service between oil changes under normal operating conditions.

TYPICAL SPECIFICATIONS								
Product Code: XL-7326	/022	/032	/046	/068	/100	/150	/220	/320
ISO Grade	22	32	46	68	100	150	220	320
Viscosity (cSt @ 40°C) (ASTM D-445)	21.5	29.3	41.5	63.5	97.2	146	210	315
(cSt @ 100°C) (ASTM D-445)	4.8	5.8	7.3	9.9	13.5	18.5	24.5	32.6
Viscosity Index	151	145	141	140	139	143	146	145
Flash Point (°C)	202	210	214	222	225	204	225	228
Pour Point (°C) (ASTM D-97)	-65	-49	-40	-40	-35	-32	-31	-28
Specific Gravity (g/ml)	0.85	0.85	0.86	0.87	0.87	0.87	0.88	0.88
Colour:	Blue							

Performance:

- Vickers 1-286-S, M-2950-S
- Denison HF-1, HF-2, HF-0
- Racine, variable volume vane pumps
- Cincinnati Milacron P-68, P-69, P-70
- DIN 51524 part 2
- Lee-Norse 100-1
- Jeffery #87
- Ford M-6C32
- US Steel 136, 127
- BF Goodrich 0152
- GM LH-04-1, LH-06-1, LH-15-1
- Commercial Hydraulics (*Except for PM-500 silver containing pumps*)
- AFNOR E 48-603

