

SYNTHETIC PAPER MACHINE OIL

The **XL-7327** series of products is formulated to meet specifications for both industrial and automotive applications where the need for high quality synthetic hydraulic oil exists.

XL-7327 is made from a careful blend of high VI (viscosity index) synthetic base-stocks and will remain stable over a wide temperature range.

XL-7327 is formulated with all the necessary additives required to meet the specifications as an anti-wear, anti-rust, anti-oxidation, high quality oil and is recommended for use in circulating hydraulic systems *including* Paper Machine Oils.

XL-7327 is available in most standard ISO viscosity grades and in a four-season multi-grade as well. As a result of the high quality of the product, we recommend up to 8,000 hours of service between oil changes under normal operating conditions.

TYPICAL SPECIFICATIONS							
Product Code: XL-7327	/022	/032	/046	/068	/100	/220	/320
ISO Grade	22	32	46	68	100	220	320
Viscosity (cSt @ 40°C) (ASTM D-445)	21.5	29.3	41.5	63.5	97.2	210	310
(cSt @ 100°C) (ASTM D-445)	4.8	5.8	7.3	9.9	13.5	24.5	32.6
Viscosity Index	151	145	141	140	139	146	145
Flash Point (°C)	202	210	214	222	225	225	228
Pour Point (°C) (ASTM D-97)	-58	-47	-40	-40	-35	-31	-28
Specific Gravity (g/ml)	0.85	0.85	0.86	0.87	0.87	0.88	0.88
Colour:	Blue						



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

