

SYNTHETIC AIR LINE OIL

XL-7328 is an extreme pressure synthetic lubricant designed for pneumatic equipment.

XL-7328 exhibits excellent anti-rust and corrosion properties and can be used in reciprocating, rotary, or impact equipment under the most severe ambient operating conditions and climates.

XL-7328 is formulated with emulsifiers and tackifiers, ensuring a high degree of resistance to wash-off, and strong adhesion to reciprocating parts.

XL-7328 is approved by the Canadian Food Inspection Agency (CFIA) for use in food processing plants.

XL-7328 is available in several standard viscosity grades to meet most air-line tool requirements.

XL-7328/022	ISO #22	light	(winter grade)
XL-7328/032	ISO #32	medium	(winter grade)
XL-7328/046	ISO #46	thick	(winter grade)
XL-7328/150	ISO #150	medium	(standard grade)
XL-7328/220	ISO #220	thick	(standard grade)

TYPICAL SPECIFICATIONS							
Product Code: XL-7328	/015	/022	/032	/046	/100	/150	/220
SAE Grade	-	-	5W	10W	30	40	50
ISO Grade	15	22	32	46	100	150	220
Viscosity (cSt @ 40°C) (ASTM D-445)	14.8	23.7	31.8	44.2	95.4	147	221
(cSt @ 100°C) (ASTM D-445)	3.6	4.8	5.8	7.3	13.5	17.3	22.0
Viscosity Index	129	126	126	128	142	128	121
Flash Point (°C)	180	182	185	188	208	215	241
Pour Point (°C) (ASTM D-97)	-55	-53	-52	-46	-38	-36	-35
Specific Gravity (g/ml)	0.83	0.86	0.86	0.87	0.88	0.89	0.90



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
 Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge, accurate. It is intended to be helpful, and is not to be considered a guarantee.

