

SYNTHETIC PAO COMPRESSOR OIL

XL-7330 series of synthetic polyalphaolefin compressor fluids are recommended for a wide range of service conditions ranging from intermittent light loads to continuous heavy duty applications.

XL-7330 fluids exhibit superior anti-wear characteristics and water tolerance, while protecting against oxidation and corrosion.

XL-7330 fluids are designed to prevent gumming, sludge, resin, and carbon formation in valves and other working parts of compressors with excellent filtration.

XL-7330 meets the strictest criteria of compressor manufacturers.

Available in all ISO standard viscosity grades or custom-formulated to suit any need.

ADVANTAGES

- Non Carbonizing
- Anti Wear, Anti Foam
- Highly Resistant to Chemical Breakdown
- High Temperature Stability

FOR USE IN

- Rotary Vane compressors
- Screw compressors
- Piston compressors

TYPICAL SPECIFICATIONS								
Product Code: XL-7330	/022	/032	/046	/068	/100	/150	/220	/922
ISO Grade	22	32	46	68	100	150	220	Multi
Viscosity (cSt @ 40°C) (ASTM D-445)	21.5	29.3	41.5	63.5	97.2	148.3	225	25.7
(cSt @ 100°C) (ASTM D-445)	4.8	5.8	7.3	9.9	13.5	18.7	25.9	6.9
Viscosity Index	151	145	141	140	139	142	147	253
Flash Point (°C)	202	210	214	222	225	225	235	208
Pour Point (°C) (ASTM D-97)	-58	-47	-40	-40	-35	-30	-32	-55
Specific Gravity (g/ml)	0.85	0.85	0.86	0.87	0.87	0.88	0.88	0.87
Colour	Blue or Clear							



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

