

## SYNTHETIC ESTER-BASED COMPRESSOR OIL

**XL-7331** is a fully formulated synthetic ester-based compressor oil for all working conditions – from light, intermittent loads to continuous heavy loads. It is designed to keep "hot" compressors "cool" and running up to 12,000 hours between oil changes. When used in conjunction with a comprehensive fluid monitoring and treatment system, fluid life can be extended up to twice as long, up to 24,000 hours.\*

**XL-7331** has incorporated a revolutionary new concept in "High Temperature" rust and oxidation inhibitors that remain active even at elevated temperatures.

**XL-7331** is designed to prevent gumming, sludge, resin, and carbon formation in valves and other working parts of compressors with excellent filtration.

### ADVANTAGES

- Non Carbonizing
- Anti Wear
- Anti Foam
- Highly Resistant to Chemical Breakdown
- High Temperature Stability

**XL-7331** meets the strictest criteria of compressor manufacturers.

\* Based on oil analysis results

TYPICAL SPECIFICATIONS							
Product Code: XL-7331	/022	/032	/046	/068	/100	/150	/220
ISO Grade	22	32	46	68	100	150	220
Viscosity (cSt @ 40°C) (ASTM D-445)	23.5	32.5	43.1	63.5	94.5	156.3	235
(cSt @ 100°C) (ASTM D-445)	4.8	5.5	6.6	8.5	11.5	16.8	24.0
Viscosity Index	128	105	105	104	110	115	128
Flash Point (°C)	202	210	214	222	225	225	248
Pour Point (°C) (ASTM D-97)	-58	-47	-40	-40	-35	-30	-18
Specific Gravity (g/ml)	0.95	0.95	0.92	0.92	0.92	0.93	0.93
Colour	Amber						



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3  
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

