

SYNTHETIC PAO COMPRESSOR OIL WITH DETERGENT

XL-7332 is a synthetic compressor lube formulated with ashless dispersants to keep "sticky" vane and screw type compressors clean.

XL-7332 is a synthetic oil formulated to keep the operating temperature of compressor rotors as low as possible. The rust and corrosion inhibitors used in the formulation remain active at high temperatures.

XL-7332 is also recommended for combustion type mobile or stationary units where blowby from the combustion has to be kept in suspension.

The **XL-7332** series of fluids will aid in restoring varnished and sludged surfaces to their original condition. An oil filter is highly recommended to remove contaminants, and increased change intervals will assure elimination of components that may cause emulsification of the fluid.

XL-7332 is available in all standard ISO grades and can also be formulated to meet individual customers' specific needs.

ADVANTAGES

- Non Carbonizing
- Anti Wear
- Anti Foam
- Highly Resistant to Chemical Breakdown
- High Temperature Stability

TYPICAL SPECIFICATIONS							
Product Code: XL-7332	/022	/032	/046	/068	/100	/150	/922
ISO Grade	22	32	46	68	100	150	Multi
Viscosity (cSt @ 40°C) (ASTM D-445)	21.5	29.3	41.5	63.5	97.2	148.3	25.7
(cSt @ 100°C) (ASTM D-445)	4.8	5.8	7.3	9.9	13.5	18.7	6.9
Viscosity Index	151	145	141	140	139	142	253
Flash Point (°C)	202	210	214	222	225	225	208
Pour Point (°C) (ASTM D-97)	-58	-47	-40	-40	-35	-30	-55
Specific Gravity (g/ml)	0.89	0.89	0.90	0.90	0.91	0.95	0.91
Colour	Amber						



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

