

REFRIGERATION COMPRESSOR OIL

XL-7337 series are high performance lubricating fluids formulated for use as refrigeration compressor oils. **XL-7337** is recommended for all working conditions, from light, intermittent loads to continuous heavy loads.

XL-7337 compressor oils contain ashless dispersants to keep "sticky" compressor valves clean.

XL-7337 offers exceptional thermal and chemical stability providing a longer life fluid with less frequent oil change-outs.

XL-7337 has been formulated to be fully compatible with most of the common refrigeration gases.

XL-7337 meets the strictest criteria of compressor manufacturers.

TYPICAL SPECIFICATIONS			
Product Code: XL-7337	/032	/068	/100
ISO Grade	32	68	100
Viscosity (cst @ 40°C) (ASTM D-445)	29.3	63.5	101.2
(cst @ 100°C) (ASTM D-445)	4.5	6.7	8.9
Flash Point (°C)	174	187	198
Pour Point (°C)	-45	-37	-21
Specific Gravity (g/ml @ 15°C) (ASTM D-1298)	0.904	0.910	0.910
Floc Point (°C)	-54	-48	-37
Dielectric Strength (kV) (ASTM D-877)	35+	35+	35+
Aniline Point (°C)	81	88	84
Sealed Tube % R-22, 14 days+	0.20	0.30	--
Colour (ASTM D-1500)	0.5	0.5	3.0



255 avenue Labrosse, Pointe-Claire, Quebec, Canada H9R 1A3
Tel: 514-694-5823 | 800-567-5823 | Fax: 514-694-8628 | www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge, accurate. It is intended to be helpful, and is not to be considered a guarantee.

